

BoatAnt™



10dB Wide Band Antenna for Amplifiers, Boosters, Repeaters, Modems, Hotspots

The BoatAnt™ is a top quality, omnidirectional antenna that can be used as an external antenna for amplifiers/repeaters/boosters (GSM/PCS/DCS/2G/3G/4G/AWS/UMTS/WiMAX), direct-connect antenna for cellular devices such as cell phones, modems, and mobile hotspots, direct-connect antenna for Wi-Fi devices, and direct-connect antenna for WiMAX devices. It is meant for the outdoors and the mount type is for pole/mast. The BoatAnt™ has a bandwidth of 700MHz to 5200MHz and a peak gain of 10.4 dB. Its nominal impedance is 50 Ohms and its connector type is N-Female. The BoatAnt™ weights 1.2 lbs (540 g) and measures 7.8 x 2.4 x 2.4 in (19.5 x 6 x 6 cm). The BoatAnt™ is a durable, high-efficiency antenna with top-notch features and performance, and it's made in the USA with high quality components and skilled craftsmanship.

Main Features

- Perfect as an external antenna for amplifiers/repeaters/boosters (GSM/PCS/DCS/2G/3G/4G/AWS/UMTS/WiMAX), direct-connect antenna for cellular devices such as cell phones, modems, and mobile hotspots, direct-connect antenna for Wi-Fi devices, and direct-connect antenna for WiMAX devices

- Very wide operational bandwidth of 700MHz to 5200MHz. Peak gain of 10.4 dB. Omnidirectional radiation type with pole/mast type mount

- Nominal impedance of 50 Ohms with vertical polarization and recommended mainly for outdoors use

- All-weather protected with wind resistance up to 140 mph (225 kmh) and operating temperature of -40°F to 185°F (-40°C to 185°C). Horizontal radiation pattern of 360°

- Made in the USA with high quality components and skilled craftsmanship. One year manufacturer warranty included

Data Sheet and Technical Specifications

Trademark Name	BoatAnt™
Part Number / SKU	BTA-50-OHM
UPC	633643376890
Applications	External antenna for amplifiers/repeaters/boosters (GSM/PCS/DCS/2G/3G/4G/AWS/UMTS/WiMAX), direct-connect antenna for cellular devices such as cell phones, modems, and mobile hotspots, direct-connect antenna for Wi-Fi devices, and direct-connect antenna for WiMAX devices
Environment	Outdoors

10dB Wide Band Antenna for Amplifiers, Boosters, Repeaters, Modems, Hotspots

Radiation Type	Omnidirectional
Mount Type	Pole/Mast
Connector Type	N-Female
Bandwidth	700MHz to 5200MHz
Nominal Gain at 750MHz	8 dB
Nominal Gain at 800MHz	8.2 dB
Nominal Gain at 850MHz	8.4 dB
Nominal Gain at 900MHz	8.6 dB
Nominal Gain at 1700MHz	9 dB
Nominal Gain at 1800MHz	9.2 dB
Nominal Gain at 1900MHz	9.4 dB
Nominal Gain at 2100MHz	9.6 dB
Nominal Gain at 2400MHz	9.8 dB
Nominal Gain at 2500MHz	10 dB
Nominal Gain at 2600MHz	10.2 dB
Nominal Gain at 2700MHz	10.4 dB
Nominal Gain at 3500MHz	11 dB
Standing Wave Ratio (VSWR) at 750MHz	1.5:1 typical (1.8:1 max)
Standing Wave Ratio (VSWR) at 800MHz	1.3:1 typical (1.6:1 max)
Standing Wave Ratio (VSWR) at 850MHz	1.1:1 typical (1.3:1 max)
Standing Wave Ratio (VSWR) at 900MHz	1.1:1 typical (1.3:1 max)
Standing Wave Ratio (VSWR) at 1700MHz	1.1:1 typical (1.3:1 max)

10dB Wide Band Antenna for Amplifiers, Boosters, Repeaters, Modems, Hotspots

Standing Wave Ratio (VSWR) at 1800MHz	1.1:1 typical (1.3:1 max)
Standing Wave Ratio (VSWR) at 1900MHz	1.1:1 typical (1.3:1 max)
Standing Wave Ratio (VSWR) at 2100MHz	1.1:1 typical (1.2:1 max)
Standing Wave Ratio (VSWR) at 2400MHz	1.2:1 typical (1.5:1 max)
Standing Wave Ratio (VSWR) at 2500MHz	1.2:1 typical (1.5:1 max)
Standing Wave Ratio (VSWR) at 2600MHz	1.2:1 typical (1.5:1 max)
Standing Wave Ratio (VSWR) at 2700MHz	1.2:1 typical (1.5:1 max)
Standing Wave Ratio (VSWR) at 3500MHz	1.2:1 typical (1.5:1 max)
Nominal Impedance	50 Ohms
Front-Back Ratio	N/A
Polarization	Vertical
Horizontal Beamwidth	360°
Vertical Beamwidth	70°
Maximum Continuous Applicable Power	115 W
Power Requirements	None (passive antenna)
Net Weight (Mount Included when applicable)	1.2 lbs (540 g)
Dimensions (Height x Width x Depth)	7.8 x 2.4 x 2.4 in (19.5 x 6 x 6 cm)
Wind Rate Resistance	140 mph (225 kmh)
Lightning Protection	Optional
Radome Material	Glass Fiber
Operating Temperature	-40°F to 185°F (-40°C to 185°C)
Other Features	All-weather protected
Production Status	Active